



## Technical Specifications

### General

|                       |                    |
|-----------------------|--------------------|
| Model Number          | : POWL 09          |
| System Watt           | : 12w              |
| Driver Integral       | : Constant Current |
| Operating Voltage     | : 120-265Vac       |
| Operating Temperature | : +10°C~+50°C      |

### Physical

|          |                                                   |
|----------|---------------------------------------------------|
| Body     | : Die-Cast Aluminium with Extruded Aluminium Tube |
| Diffuser | : Milky Polycarbonate                             |
| Gasket   | : Silicone                                        |
| Mounting | : Surface / floor mounted                         |
| Finish   | : Powder coated<br>RAL 7016 Graphite Grey         |



12w



### Light Source

|                        |                          |
|------------------------|--------------------------|
| Light Source           | : Bridgelux LED / Edison |
| CRI (Ra)               | : ≥80                    |
| LED Colour Temperature | : 3000K                  |

### Driver

|                      |                     |
|----------------------|---------------------|
| Power Supply         | : Integral          |
| Input Voltage        | : 130-265VAC        |
| Frequency            | : 50Hz              |
| Power Factor         | : ≥0.5              |
| Surge Protection     | : 2 KV              |
| Efficiency           | : >80%              |
| Driver Specification | : DC 24 - 40V 300mA |
| Luminous Flux (LM)   | : 1200lm(± 10% lm)  |

### Optical Performance

|                    |               |
|--------------------|---------------|
| Light Distribution | : Symmetrical |
|--------------------|---------------|



Designed to bring a sleek, architectural touch to your space, this modern minimalist wall sconce features a clean C-frame silhouette that frames a central cylindrical diffuser. Its textured dark matte finish and geometric profile make it an ideal accent for modern home exteriors, patios, entryways, or interior corridors.

## Product Description

- Product Type: LED Wall Light / Modern Wall Sconce
- Mounting: Surface-mounted on wall
- Design: Contemporary lamp-shade silhouette / architectural accent
- Housing: Durable metal/aluminium construction
- Finish: Textured dark grey / charcoal finish
- Light Distribution: Downward wall wash with ambient rim glow
- Light Distribution: 360-degree ambient surrounding illumination
- Recommended Locations: Living rooms, bedrooms, corridors, entryways, staircases, and indoor feature walls  
Style: Modern, minimalist, and elegant
- CRI (Ra): ≥80 CCT: 3000K warm white.



## Product Benefits

- Warm Ambient Illumination Creates an inviting, comfortable atmosphere with smooth downward lighting and a soft lower rim accent.
- Classic Shade Design The conical flared shade profile offers a timeless, sophisticated look that elevates modern interior spaces
- Glare-Free Visual Comfort The translucent frosted rim diffuses light evenly to reduce eye strain and provide glare-free illumination.
- Energy Efficient LED Integrated LED technology delivers bright performance while maintaining lower energy consumption compared to traditional lamp
- Durable Metal Construction Crafted with a sturdy, textured aluminum frame designed for long-lasting stability and wear resistance.
- Easy Surface Mounting Designed for straightforward installation directly onto standard indoor wall points.

## Area of Application

Residential & Commercial Buildings / Offices & Retail Spaces / Corridors, Entrances & Walkways

## Available Finish

Pure polyester powder coated

RAL 7016 Graphite Grey