



Technical Specifications

General

Model Number	: POWL 57
System Watt	: 2X4w
Driver Integral	: Constant Current
Operating Voltage	: 130-265Vac
Operating Temperature	: +10°C~+50°C

Physical

Body	: Die-Cast Aluminium with Extruded Aluminium Tube
Diffuser	: Milky Polycarbonate
Gasket	: Silicone
Mounting	: Surface / wall mounted
Finish	: Powder coated RAL 9007 Grey



Light Source

Light Source	: Edison / Bridgelux LED / Epistar
CRI (Ra)	: ≥80
LED Colour Temperature	: 3000K

Driver

Power Supply	: Integral
Input Voltage	: 130-265VAC
Frequency	: 50Hz
Power Factor	: ≥0.5
THD	: ≥150%
Surge Protection	: 4 KV
Efficiency	: >80%
Driver Specification	: DC 28-40V 300mA
Luminous Flux (LM)	: 400lm(± 10% lm)

Optical Performance

Light Distribution	: Symmetrical
--------------------	---------------



The Wall Light is a compact, square-shaped architectural sconce designed to provide dual-directional illumination. Built with a durable powder-coated aluminum housing in a matte graphite grey finish, it features top and bottom diffusers that cast soft light beams against vertical surfaces. Its minimalist design integrates seamlessly onto exterior walls, pillars, and entryways to highlight textured stone, brick, or rendered facades.

Product Description

- **Product Type:** Modern square-shaped surface-mounted wall sconce designed for exterior and interior lighting
- **Dual-Directional Output:** Features top and bottom light channels to project illumination both upward and downward against wall surfaces.
- **Design & Finish:** Features a compact, rounded-edge square profile with a matte graphite grey body and a subtle lower logo imprint.
- **Material & Build:** Constructed with a durable, weather-resistant outer shell and sealed diffusers to withstand outdoor elements.
- **Lighting Effect:** Delivers an architectural wash effect, ideal for highlighting textured brick, stone, or rendered surfaces on facades, pillars, and entryways.
- Easy to install on walls..
- CRI (Ra): ≥80 CCT: 3000K warm white.



Product Benefits

- **Dual-Directional Illumination:** Casts light both upwards and downwards, creating a decorative visual effect that enhances architectural features and safety.
- **Weather-Resistant Build:** Constructed with a rugged metal body and rated for outdoor protection against rain, moisture, and dust exposure.
- **Energy-Efficient LED Technology:** Delivers warm white light with low power consumption and long-lasting performance.
- **Modern & Minimalist Aesthetic:** The flush, surface-mounted square form complements modern residential and commercial exterior designs.
- **Reduced Glare:** Top and bottom diffusers soften the beam, providing comfortable ambient light without direct harsh glare.
- **Low Maintenance** – Provides long-lasting and dependable lighting.

Area of Application

Residential & Commercial Buildings / Offices & Retail Spaces / Gardens, Pathways & Outdoor Areas

Available Finish

Pure polyester powder coated
RAL 9007 Grey