



Technical Specifications

General

Model Number	: POWL 61
System Watt	: 8w
Driver Integral	: Constant Current
Operating Voltage	: 130-265Vac
Operating Temperature	: +10°C~+50°C

Physical

Body	: Die-Cast Aluminium with Extruded Aluminium Tube
Diffuser	: Clear Polycarbonate
Gasket	: Silicone
Mounting	: Surface / wall mounted
Finish	: Powder coated RAL 9007 Grey



Light Source

Light Source	: Cree / Bridgelux LED / Epistar
CRI (Ra)	: ≥80
LED Colour Temperature	: 3000K

Driver

Power Supply	: Integral
Input Voltage	: 130-265VAC
Frequency	: 50Hz
Power Factor	: ≥0.5
THD	: ≥150%
Surge Protection	: 2 KV
Efficiency	: >80%
Driver Specification	: DC 9-18V 350mA
Luminous Flux (LM)	: 800lm(± 10% lm)

Optical Performance

Light Distribution	: Symmetrical
--------------------	---------------



This modern outdoor wall light combines a classic architectural design with functional exterior illumination. Its downward-facing shade provides comfortable, focused light while reducing direct glare. The elegant black finish complements contemporary and traditional façades, making it suitable for entrances, patios, balconies, pathways, gardens, and exterior walls

Product Description

- Modern and compact LED wall light with a sleek oval design.
- Provides smooth upward and downward illumination for an attractive wall-wash effect.
- Creates a stylish architectural lighting effect on walls and façades.
- Suitable for both indoor and outdoor decorative applications.
- Ideal for entrances, balconies, corridors, patios, gardens, hotels and commercial spaces
- Easy to install on walls..
- CRI (Ra): ≥80 CCT: 3000K warm white.



Product Benefits

- Modern aesthetics – Enhances walls and building façades with a premium look.
- Up & down lighting – Provides layered illumination for a balanced lighting effect.
- Architectural highlighting – Brings out wall textures and architectural details.
- Energy efficient – LED technology provides efficient illumination with lower energy consumption..
- Low maintenance – LED light sources generally offer long operating life and reduce frequent replacement.
- Improved safety – Helps illuminate entrances, pathways and outdoor circulation areas..

Area of Application

Residential & Commercial Buildings / Offices & Retail Spaces / Gardens, Pathways & Outdoor Areas

Available Finish

Pure polyester powder coated
RAL 9007 Grey