PASOLITE






Technical Specifications

General


Model Number	:	POWL 67 / POWL 68
System Watt	:	3w / 2X3W
Driver Integral	:	Constant Current
Operating Voltage	:	130-265Vac
Operating Temperature	:	+10°C~+50°C

Physical

Body	: Die-Cast Aluminium with Extruded Aluminium Tube
Diffuser	: Clear Polycarbonate lens
Gasket	: Silicone
Mounting	: Surface / wall mounted
Finish	: Powder coated RAL 9007 Grey



3w (1 WAY)



2X3w (2 WAY)

Narrow beam

IP54 Ik08



Light Source

Light Source	: Cree / Bridgelux LED / Epistar
CRI (Ra)	: ≥80
LED Colour Temperature	: 3000K

Driver

Power Supply	: Integral
Input Voltage	: 130-265VAC
Frequency	: 50Hz
Power Factor	: ≥0.4 / ≥0.5
THD	: ≥200%
Surge Protection	: 2 KV
Efficiency	: >82% / >80%
Driver Specification	: DC 03-6V 700mA / DC 3-6V 700mA
Luminous Flux (LM)	: 300lm(± 10% lm) / 600lm(± 10% lm)

Optical Performance

Light Distribution	: Symmetrical

Note : It is our constant endeavor to upgrade the performance of our products. For the latest technical information, product updates please refer to the website at www.pasolite.in

PASOLITE

This modern 2-way outdoor wall sconce features a sleek, rectangular die-cast housing designed to cast focused narrow beams of light simultaneously upward and downward. Equipped with specialized optical lenses, it creates sharp, architectural light columns that beautifully highlight building facades, pillars, and textured walls without causing glare. Its weather-resistant and waterproof IP-rated body ensures long-lasting durability against harsh environmental conditions like rain, heat, and dust. Combining low power consumption with high visual impact, it serves as an energy-efficient solution for both decorative accenting and outdoor safety illumination.



Product Description

- Single and Dual-Direction Illumination: Projects a focused single beam of light both upward and downward, creating a dramatic and elegant visual effect on any vertical surface.
- Focused Narrow Beam Lenses: Uses specialized optical lenses to project sharp, concentrated light lines instead of wide, scattered illumination.
- Sleek Modern Aesthetics: Features a minimal rectangular body with textured accent grooves, blending into modern interior and exterior architecture.
- All-Weather IP Rating: Constructed with a sealed die-cast body designed to protect against water, rain, heat, and dust.
- Low-Power High-Output LED: Integrates energy-efficient LED modules to deliver maximum contrast and brightness with minimal energy draw.
- Easy to install on walls..
- CRI (Ra): ≥80 CCT: 3000K warm white.

IP54 IK08

Product Benefits

- Architectural Wall Accentuation: Highlights wall textures, brickwork, stone facades, and outdoor pillars by drawing clean vertical lighting lines
- Dual-Sided Lighting Balance: Provides balanced upper and lower wall coverage in one fixture, reducing the need for multiple lights.
- Long-Term Outdoor Durability: Rust-proof and weather-resistant construction ensures reliable, maintenance-free operation in outdoor environments.
- Glares-Free Visual Comfort: The focused beam directs light cleanly along the wall surface without shining uncomfortably into eyes.
- Energy-Efficient Operation: LED chips deliver high-intensity light while keeping power consumption low for long daily use.

Area of Application

Hotels, Villas & Hospitality Spaces / Residential & Commercial Exteriors / Gardens, Pathways & Entrances

Available Finish

RAL 9007 Grey