PASOLITE






Technical Specifications

General

Model Number	:	POWL 70
System Watt	:	10w (2 way)
Driver Integral	:	Constant Current
Operating Voltage		: 130-265Vac
Operating Temperature		: +10°C~+50°C




10w (2 WAY)

Physical

Body	: Die-Cast Aluminium with Extruded Aluminium Tube
Diffuser	: Clear Glass
Gasket	: Silicone
Mounting	: Surface / wall mounted
Finish	: Powder coated White

IP54 | Ik08



Light Source

Light Source	: Cree / Bridgelux LED / Epistar
CRI (Ra)	: ≥80
LED Colour Temperature	: 3000K

Driver

Power Supply	: Integral
Input Voltage	: 130-265VAC
Frequency	: 50Hz
Power Factor	: ≥0.55
THD	: ≥120%
Surge Protection	: 2 KV
Efficiency	: >82%
Driver Specification	: DC 30-38V 280mA
Luminous Flux (LM)	: 1000lm(± 10% lm)

Optical Performance

Light Distribution	: Symmetrical

Note : It is our constant endeavor to upgrade the performance of our products. For the latest technical information, product updates please refer to the website at www.pasolite.in

PASOLITE

This modern 2-way outdoor wall sconce features a sleek, rectangular die-cast housing designed to cast focused narrow beams of light simultaneously upward and downward. Equipped with specialized optical lenses, it creates sharp, architectural light columns that beautifully highlight building facades, pillars, and textured walls without causing glare. Its weather-resistant and waterproof IP-rated body ensures long-lasting durability against harsh environmental conditions like rain, heat, and dust. Combining low power consumption with high visual impact, it serves as an energy-efficient solution for both decorative accenting and outdoor safety illumination.



Product Description

- Architectural Dual-Emission Design: Features simultaneous upward and downward light distribution to create a dramatic wash of ambient light against vertical surfaces.
- Sleek Minimalist Aesthetic: Designed with a clean, low-profile oval silhouette and a durable white powder-coated exterior frame with a contrasting dark glass faceplate.
- High-Efficiency Integrated LED: Built with top-strip LED arrays for upward illumination and precision optical lenses for downward lighting..
- All-Weather Construction: Engineered for exterior and interior use with weather-resistant sealing to withstand dust and moisture exposure.
- Soft Warm-Tone Glow: Delivers a warm, inviting color temperature suitable for accentuating architectural details, stone facades, or textured walls.
- Easy to install on walls..
- CRI (Ra): ≥80 CCT: 3000K warm white.

IP54 IK08

Product Benefits

- Enhanced Curb Appeal: Instantly elevates outdoor facades, entryways, patios, and garden walls with high-end, gallery-style light patterns.
- Custom Beam Pattern: Softens top glare while casting a wide, high-contrast glow downwards for safe pathway and floor-level illumination.
- Energy Efficient: Consumes minimal wattage while providing bright, high-lumen coverage compared to traditional halogen fixtures.
- Low Maintenance: Integrated LEDs eliminate the need for frequent bulb replacements and offer long operational life spans.
- Versatile Mounting: Compact depth keeps it flush to the wall, making it ideal for narrow corridors, stairwells, or outdoor perimeter lighting without obstructing walkways.

Area of Application

Residential & Commercial Buildings / Offices & Retail Spaces / Corridors, Entrances

Available Finish

Powder coated

White