




Technical Specifications

General

Model Number	: POWL 93
System Watt	: 2X1w
Driver Integral	: Constant Current
Operating Voltage	: 130-265Vac
Operating Temperature	: +10°C ~ +50°C

Physical

Body	: Die-Cast Aluminium with
Diffuser	: Clear Polycarbonate Lens
Gasket	: Silicone
Mounting	: Surface / wall mounted
Finish	: Powder coated RAL 9007 Grey



2X1w

Light Source

Light Source	: Cree / Bridgelux LED
CRI (Ra)	: ≥80
LED Colour Temperature	: 3000K



Driver

Power Supply	: Integral
Input Voltage	: 130-265VAC
Frequency	: 50Hz
Power Factor	: ≥0.57
Surge Protection	: 2 KV
Efficiency	: >70%
Driver Specification	: DC6-12V 250mA
Luminous Flux (LM)	: 200lm(± 10% lm)

Optical Performance

Light Distribution	: Symmetrical
--------------------	---------------



A contemporary spherical wall light designed to deliver distinctive up-and-down directional illumination with a dramatic architectural effect. The sleek rounded housing creates a refined modern appearance, while the focused light distribution produces attractive geometric patterns on textured walls. Ideal for enhancing façades, entrances, patios, pathways, and landscape areas.

Product Description

- Premium wall light designed for elegant outdoor illumination.
- Produces a focused, warm light beam in both upward and downward directions.
- Compact design blends easily with modern architectural exteriors.
- Perfect for gardens, pathways, entrances, balconies, and building façades.
- Suitable for indoor and outdoor applications
- Ideal for façades, entrances and feature walls
- Easy to install on walls
- CRI (Ra): ≥80 CCT: 3000K warm white.



Product Benefits

- Stylish and modern wall-mounted design
- Creates a beautiful up-and-down light effect.
- Enhances exterior walls with decorative illumination
- Ideal for residential and commercial outdoor spaces
- Durable construction for long-lasting performance
- Decorative & Functional: Combines stylish appearance with practical illumination.

Area of Application

Residential & Villa Exteriors / Hotel & Commercial Building Facades
/ Entrances, Pathways & Outdoor Areas

Available Finish

Powder coated
RAL 9007 Grey