PASOLITE





Technical Specifications

General

Model Number	:	POWL 99
System Watt	:	10w
Driver Integral	:	Constant Current
Operating Voltage		: 130-265Vac
Operating Temperature		: +10°C ~ +50°C


Physical

Body	: Die-Cast Aluminium with Extruded Aluminium Tube
Diffuser	: Milky Polycarbonate
Gasket	: Silicone
Mounting	: Surface / wall mounted
Finish	: Powder coated RAL 9016 Graphite Grey



10w

IP54 Ik08



Light Source

Light Source	: Edison / Bridgelux LED / Epistar
CRI (Ra)	: ≥80
LED Colour Temperature	: 3000K

Driver

Power Supply	: Integral
Input Voltage	: 130-265VAC
Frequency	: 50Hz
Power Factor	: ≥0.85
THD	: ≥13%
Surge Protection	: 2 KV
Efficiency	: >85%
Driver Specification	: DC12-30V 300mA
Luminous Flux (LM)	: 1000lm(± 10% lm)

Optical Performance

Light Distribution	: Symmetrical

Note : It is our constant endeavor to upgrade the performance of our products. For the latest technical information, product updates please refer to the website at www.pasolite.in

Slimline wall light designed with a sleek, contemporary profile for modern interiors and exteriors. Provides soft, uniform illumination with a clean and elegant visual effect. Ideal for corridors, bedrooms, living spaces, entrances, and architectural walls. Durable construction ensures reliable performance with a refined decorative finish.



Product Description

- Sleek linear LED wall light
- Ultra-slim profile for a modern appearance
- Provides smooth and uniform illumination
- Designed for elegant architectural wall lighting
- Suitable for bedrooms, corridors, living spaces and offices
- Ideal for residential, hospitality and commercial applications
- Easy to install on walls
- CRI (Ra): ≥80 CCT: 3000K warm white.

IP54 IK08

Product Benefits

- Slim and elegant linear design
- Uniform, soft light distribution
- Energy-efficient LED technology
- Modern and minimalist appearance
- Space-saving wall-mounted construction
- Provides comfortable glare-free illumination

Area of Application

Residential & Villa Exteriors / Hotel & Commercial Building Facades / Entrances, Pathways & Outdoor Areas

Available Finish

Powder coated

RAL 9016 Graphite Grey