PASOLITE





Technical Specifications

General

Model Number	:	POWL 63 / POWL 64
System Watt	:	12w / 2X12W
Driver Integral	:	Constant Current
Operating Voltage	:	130-265Vac
Operating Temperature	:	+10°C~+50°C

Physical

Body	: Die-Cast Aluminium with Extruded Aluminium Tube
Diffuser	: Clear Glass Reflector
Gasket	: Silicone
Mounting	: Surface / wall mounted
Finish	: Powder coated RAL 9007 Grey



12w



2X12w

IP54 Ik08



Light Source

Light Source	: Cree / Bridgelux LED / Epistar
CRI (Ra)	: ≥80
LED Colour Temperature	: 3000K

Driver

Power Supply	: Integral
Input Voltage	: 130-265VAC
Frequency	: 50Hz
Power Factor	: ≥0.52 , 0.98
THD	: ≥50% /≤10%
Surge Protection	: 4 KV
Efficiency	: >82% / >85%
Driver Specification	: DC 24-42V 300mA / DC 24-40V 600mA
Luminous Flux (LM)	: 1200lm(± 10% lm) / 2400lm(± 10% lm)

Optical Performance

Light Distribution	: Symmetrical

Note : It is our constant endeavor to upgrade the performance of our products. For the latest technical information, product updates please refer to the website at www.pasolite.in

PASOLITE

This sleek, modern cylindrical outdoor wall sconce features a durable dark gray finish designed to complement contemporary home exteriors. Equipped with an integrated reflector lens, it projects a warm, ambient downward glow that beautifully illuminates textured stone walls, entryways, and patio areas. Its weather-resistant construction ensures reliable, energy-efficient performance against the elements while adding a sophisticated architectural touch to any outdoor space.



Product Description

- Modern wall-mounted spotlight designed for focused and directional illumination.
- Compact cylindrical housing with a clean, contemporary appearance suitable for architectural spaces
- Adjustable spotlight positioning helps direct light toward walls, plants, pathways, entrances, or façade features.
- Ideal for residential, commercial, hospitality, garden, and landscape applications.
- Creates an attractive accent-lighting effect while enhancing the visual appeal of outdoor spaces.
- Easy to install on walls..
- CRI (Ra): ≥80, ≥90 is Available ,CCT: 3000K warm white

IP54 IK08

Product Benefits

- Focused Illumination – Provides precise light where it is needed.
- Adjustable Direction – Allows flexible aiming to highlight architectural or landscape features.
- Modern Design – Sleek cylindrical form complements contemporary exteriors.
- Enhanced Ambience – Adds decorative accent lighting while improving nighttime visibility..
- Low maintenance – LED light sources generally offer long operating life and reduce frequent replacement.
- Versatile Application – Suitable for walls, entrances, gardens, pathways, façades, and landscape features.

Area of Application

Hotels, Villas & Hospitality Spaces / Residential & Commercial Exteriors / Gardens, Pathways & Entrances

Available Finish

Pure polyester powder coated

RAL 9007 Grey

PASOLITE





Technical Specifications

General

Model Number	:	POWL 65 / POWL 66
System Watt	:	6w / 2X6W
Driver Integral	:	Constant Current
Operating Voltage	:	130-265Vac
Operating Temperature	:	+10°C~+50°C

Physical

Body	: Die-Cast Aluminium with Extruded Aluminium Tube
Diffuser	: Clear Glass Reflector
Gasket	: Silicone
Mounting	: Surface / wall mounted
Finish	: Powder coated RAL 9007 Grey RAL 9004 Black



6w



2X6w

IP54 Ik08



Light Source

Light Source	: Cree / Bridgelux LED / Epistar
CRI (Ra)	: ≥80
LED Colour Temperature	: 3000K

Driver

Power Supply	: Integral
Input Voltage	: 130-265VAC
Frequency	: 50Hz
Power Factor	: ≥0.5 / ≥0.98
THD	: ≥150% / ≤ 10%
Surge Protection	: 4 KV
Efficiency	: >82% / >85%
Driver Specification	: DC 15-21V 300mA / DC 24-45V 300mA
Luminous Flux (LM)	: 600lm(± 10% lm) / 1200lm(± 10% lm)

Optical Performance

Light Distribution	: Symmetrical

Note : It is our constant endeavor to upgrade the performance of our products. For the latest technical information, product updates please refer to the website at www.pasolite.in

PASOLITE

This modern cylindrical outdoor wall light features a dual-directional design that casts a warm, inviting glow both upward and downward. Engineered with a durable matte dark gray body and integrated reflector lenses, it creates wide, soft V-shaped light spreads that accentuate exterior walls, entrance pillars, and garden walkways. Built to withstand all weather conditions, its sleek architectural style effortlessly enhances modern home exteriors while delivering reliable, energy-efficient illumination.



Product Description

- Modern wall-mounted spotlight designed for focused and directional illumination.
- Compact cylindrical housing with a clean, contemporary appearance suitable for architectural spaces
- Adjustable spotlight positioning helps direct light toward walls, plants, pathways, entrances, or façade features.
- Ideal for residential, commercial, hospitality, garden, and landscape applications.
- Creates an attractive accent-lighting effect while enhancing the visual appeal of outdoor spaces.
- Easy to install on walls..
- CRI (Ra): ≥80, ≥90 is Available ,CCT: 3000K warm white

IP54 IK08

Product Benefits

- Focused Illumination – Provides precise light where it is needed.
- Adjustable Direction – Allows flexible aiming to highlight architectural or landscape features.
- Modern Design – Sleek cylindrical form complements contemporary exteriors.
- Enhanced Ambience – Adds decorative accent lighting while improving nighttime visibility..
- Low maintenance – LED light sources generally offer long operating life and reduce frequent replacement.
- Versatile Application – Suitable for walls, entrances, gardens, pathways, façades, and landscape features.

Area of Application

Hotels, Villas & Hospitality Spaces / Residential & Commercial Exteriors / Gardens, Pathways & Entrances

Available Finish

Pure polyester powder coated
RAL 9007 Grey
RAL 9004 Black